



# NYPLA INDUSTRIAL CO., LTD.

TEL: 626-6264889 FAX: 626-6264898  
http://www.nypla.com

## Product Information

## NYLOY<sup>®</sup> MG-0034N-V0 B14

- Nylon 66
- 33.5% Glass Fiber Reinforced/Flame Retardant
- Black

| PROPERTY                             | METHOD       | UNIT              | RESULT |
|--------------------------------------|--------------|-------------------|--------|
| <b>MECHANICAL</b>                    |              |                   |        |
| Tensile Strength                     | ISO 527      | MPa               | 123    |
| Elongation                           | ISO 527      | %                 | 1.5    |
| Flexural Strength                    | ISO 178      | MPa               | 180    |
| Flexural Modulus                     | ISO 178      | MPa               | 9200   |
| Charpy Impact, Notched 23° C         | ISO 179/ 1eA | kJ/m <sup>2</sup> | 8      |
| Charpy Impact, Notched -20°C         | ISO 179/ 1eA | kJ/m <sup>2</sup> | -      |
| Hardness Rockwell R Scale            | ISO 2039     | -                 | -      |
| Hardness Shore D                     | ISO 868      | -                 | -      |
| <b>THERMAL</b>                       |              |                   |        |
| Heat Deflection Temp                 | ISO 75       |                   |        |
| 1.82MPa                              |              | °C                | 230    |
| 0.46MPa                              |              | °C                | -      |
| <b>OTHER</b>                         |              |                   |        |
| Density                              | ISO 1183     | g/cm <sup>3</sup> | -      |
| Mold Shrinkage                       | ISO 294-4    |                   | -      |
| Normal                               |              | %                 | 1.05   |
| Parallel                             |              | %                 | 0.39   |
| Ash Content                          | -            | %                 | 34     |
| Flammability                         | UL-94        | 1.6mm             | -      |
|                                      | UL-94        | 3.2mm             | V0     |
| <b>REMARK</b>                        |              |                   |        |
| (1) This data is for reference only. |              |                   |        |