



NYPLA INDUSTRIAL CO., LTD.

TEL: 626-6264889 FAX: 626-6264898
<http://www.nypla.com>

Product Information

NYLOY[®] CM-5000 8045B2

• Nylon • Thermal and electrical conductive flame retardant grade • Black

PROPERTY	METHOD	UNIT	RESULT
MECHANICAL			
Tensile Strength	ASTM D638	kg/cm ²	900
Elongation	ASTM D638	%	1.3
Flexural Strength	ASTM D790	kg/cm ²	1400
Flexural Modulus	ASTM D790	kg/cm ²	135000
IZOD Impact, Notched 1/8" 23°C	ASTM D256	kg-cm/cm	5.0
THERMAL			
Heat Deflection Temp (18.6kg/cm ²) (1.82MPa)	ASTM D648	°C	205
Conductivity	ISO 22007-2	W/m*K	4.5
ELECTRICAL			
Surface Resistance	ASTM D4496	Ohm-P-SQ	10 ⁵
OTHER			
Density	ASTM D792	g/cm ³	1.52
Mold Shrinkage	ASTM D955		
//flow		%	0.2
⊥flow		%	0.4
Flammability	UL-94	3.2mm	V0
REMARK			
(1)This data is for reference only.			