



# NYPLA INDUSTRIAL CO., LTD.

TEL: 626-6264889 FAX: 626-6264898  
http://www.nypla.com

## Product Information

## NYLOY<sup>®</sup> D-0020N-V B3

• PC/ABS • Flame Retardant • Black

PROPERTY	METHOD	UNIT	RESULT
<b>MECHANICAL</b>			
Tensile Strength	ASTM D638	kg/cm <sup>2</sup> (MPa)	629 (52.86)
Elongation	ASTM D638	%	49
Flexural Strength	ASTM D790	kg/cm <sup>2</sup> (MPa)	1119 (87.87)
Flexural Modulus	ASTM D790	kg/cm <sup>2</sup> (MPa)	2.87x10 <sup>4</sup> (2236)
IZOD Impact, Notched 1/8" 23°C	ASTM D256	kg-cm/cm (J/M)	64.3 (630.33)
IZOD Impact, Notched 1/8" -20°C	ASTM D256	kg-cm/cm (J/M)	-
Hardness Rockwell R Scale	ASTM D785	-	-
Hardness Shore D	ASTM D2240	-	-
<b>THERMAL</b>			
Heat Deflection Temp	ASTM D648		
(18.6kg/cm <sup>2</sup> ) (1.82MPa)		°C	85
(4.6kg/cm <sup>2</sup> ) (0.46MPa)		°C	95
<b>OTHER</b>			
Density	ASTM D792	g/cm <sup>3</sup>	1.175
Mold Shrinkage	ASTM D955	%	0.7
Moisture Contents	-	%	-
Flammability	UL-94	1.6mm	V0
	UL-94	3.2mm	-
<b>REMARK</b>			
(1) This data is for reference only.			