



# NYPLA INDUSTRIAL CO., LTD.

TEL: 626-6264889 FAX: 626-6264898  
http://www.nypla.com

## Product Information

## NYLOY<sup>®</sup> MS-0100N

• Nylon 66 • Impact Modified • Natural

PROPERTY	METHOD	UNIT	RESULT
MECHANICAL			
Tensile Strength	ISO 527	MPa	40
Elongation	ISO 527	%	120
Flexural Strength	ISO 178	MPa	54
Flexural Modulus	ISO 178	MPa	1300
Charpy Impact, Notched 23° C	ISO 179/ 1eA	kJ/m <sup>2</sup>	100
Charpy Impact, Notched -20°C	ISO 179/ 1eA	kJ/m <sup>2</sup>	80
Hardness Rockwell R Scale	ISO 2039	-	-
Hardness Shore D	ISO 868	-	D-72
THERMAL			
Heat Deflection Temp	ISO 75		
1.82MPa		°C	-
0.46MPa		°C	-
OTHER			
Density	ISO 1183	g/cm <sup>3</sup>	1.06
Mold Shrinkage	ISO 294-4		-
Normal		%	1.68
Parallel		%	1.53
Ash Content	-	%	-
REMARK			
(1) This data is for reference only.			