



# NYPLA INDUSTRIAL CO., LTD.

TEL: 626-6264889 FAX: 626-6264898  
http://www.nypla.com

## Product Information

## NYLOY<sup>®</sup> MG-0050N

- Nylon 66 • 50%Glass Fiber Reinforced • Natural

| PROPERTY                             | METHOD     | UNIT               | RESULT     |
|--------------------------------------|------------|--------------------|------------|
| <b>MECHANICAL</b>                    |            |                    |            |
| Tensile Strength                     | ASTM D638  | psi                | 32005.69   |
| Elongation                           | ASTM D638  | %                  | 1.5        |
| Flexural Strength                    | ASTM D790  | psi                | 42674.25   |
| Flexural Modulus                     | ASTM D790  | psi                | 1792318.63 |
| IZOD Impact, Notched 1/8" 73.4°F     | ASTM D256  | ft-lb/in           | 3.49       |
| IZOD Impact, Notched 1/8" -4°F       | ASTM D256  | ft-lb/in           | -          |
| Hardness Rockwell R Scale            | ASTM D785  | -                  | R-120      |
| Hardness Shore D                     | ASTM D2240 | -                  | -          |
| <b>THERMAL</b>                       |            |                    |            |
| Heat Deflection Temp                 | ASTM D648  |                    |            |
| 264 psi                              |            | °F                 | 491        |
| 66 psi                               |            | °F                 | -          |
| <b>OTHER</b>                         |            |                    |            |
| Density                              | ASTM D792  | lb/in <sup>3</sup> | 0.0482     |
| Mold Shrinkage                       | ASTM D955  |                    | -          |
| Normal                               |            | %                  | 1.13       |
| Parallel                             |            | %                  | 0.48       |
| Moisture Contents                    | -          | %                  | -          |
| <b>REMARK</b>                        |            |                    |            |
| (1) This data is for reference only. |            |                    |            |